010-09-05

Aerodrome signs: key figures

7 figures in 4 groups. Read the cue, say the figure, then check. Each group ends with a recap.
Rules change: check the regulation in force.

PPL Knowledge · © rpvfalmeida · CC BY-NC-ND 4.0 Educational content. It does not replace ATO instruction.

RVR below which signs are illuminated

800 m RVR

Signs are illuminated when used below this RVR

Night, non-instrument runway, code number 3 or 4

Code number 3 or 4

Signs are illuminated

Night, non-instrument runway, code number 1 or 2

Code number 1 or 2

Signs are retroreflective and/or illuminated

Illumination: recap

CUE	FIGURE	DETAIL
RVR below which signs are illuminated	**800 m RVR**	Signs are illuminated when used below this RVR
Night, non-instrument runway, code number 3 or 4	**Code number 3 or 4**	Signs are illuminated
Night, non-instrument runway, code number 1 or 2	**Code number 1 or 2**	Signs are retroreflective and/or illuminated

Paved instrument runway length for the EU aerodrome rules

800 m

Open to public use and serving commercial air transport

Scope: recap

CUE	FIGURE	DETAIL
Paved instrument runway length for the EU aerodrome rules	800 m	Open to public use and serving commercial air transport

Pattern of the runway vacated sign panel

2 lines + 2 rows

Two continuous black lines in the upper half, then two rows of black dashes

VOR check-point sign example values

116.3 · 147° · 4.3 NM

Illustrative only; frequency, bearing and DME distance on the sign

Information signs: recap

CUE	FIGURE	DETAIL
Pattern of the runway vacated sign panel	**2 lines + 2 rows**	Two continuous black lines in the upper half, then two rows of black dashes
VOR check-point sign example values	**116.3 · 147° · 4.3 NM**	Illustrative only; frequency, bearing and DME distance on the sign

VOR check-point bearing tolerance for operational use

±2°

ICAO note; consistent with the stated bearing

ICAO-only signs: recap

CUE	FIGURE	DETAIL
VOR check-point bearing tolerance for operational use	±2°	ICAO note; consistent with the stated bearing